

OFFICE OF THE MARION COUNTY SURVEYOR

SECTION RECORD CORNER

SECTION 29 TOWNSHIP 16 RANGE 5

DATE: 5-26-04

PARTY CHIEF: Wilcoxon

CREW: _____

TYPE OF MARKER: Harrison

METHOD OF ESTABLISHMENT: County: 11-12-97


IN. S.P.C. E ZONE NAD '83

NAME: 16052905

N: 505823.8930(m)

E: 71447.3610(m)

NOTE: This corner position represents a title corner and may not necessarily be in the position of the Record corner.



Survey by D.B. Hosbrook on March 28, 1853 indicates no stone but following witness: 36" elm N 10 W 10 links, 28" elm N 89 E 13 links per Warren Township Legal Survey Book pg. 14. MCSO 8-21-45 called stone. Schmidt 8-27-51 called stone 12" down. 2-10-70 called railroad spike w/cut 'x' over stone 12" down. Fortner 4-8-75 called RR spike. Levering 5-6-83 called same. Gries 7-18-88 called same. Wilcoxon 4-4-96 called railroad spike 5" down. Wilcoxon excavated corner and set Harrison in position of the stone. Re-tied 11-12-97 by Wilcoxon. Re-tied 5-26-04 by Wilcoxon.

16052905

REF.	DISTANCE	DESCRIPTION
1.	56.31'	Top nut of fire hydrant
2.	20.00'	Due E to C/L of Jill Drive
3.	89.92'	Mag nail w/brass washer N PwP#16-481 BA 8"up
4.	18.47'	Mag nail w/brass washer NW PwP#22-481 B 8"up
5.	25.89'	Cut 'x' in W-rim of sewer manhole
6.	77.51'	SE corner of brick ADDRESS 9442